



Rival Aluminum Plates

| Plate size | Boot size | Plate length in mm | Wheelbase in mm | Toe length* in mm | Heel length** in mm | Plate length in inches | Wheelbase in inches | Plate weight each / pair in ounces | Plate weight assembly*** each / pair in ounces |
|------------|------------|-----------------------|--------------------|----------------------|------------------------|---------------------------|------------------------|--|--|
| 2 | 2, 2 1/2 | 214 | 128 | 57 | 29 | 8 2/5 | 5 1/20 | 6.40 / 12.80 | 16.32 / 32.64 |
| 3 | 3, 3 1/2 | 222 | 134 | 59 | 29 | 8 3/4 | 5 1/4 | 6.52 / 13.04 | 16.44 / 32.88 |
| 4 | 4, 4 1/2 | 230 | 140 | 61 | 29 | 9 1/20 | 5 1/2 | 6.72 / 13.44 | 16.64 / 33.28 |
| 5 | 5, 5 1/2 | 238 | 146 | 63 | 29 | 9 2/5 | 5 3/4 | 6.92 / 13.84 | 16.84 / 33.68 |
| 6 | 6, 6 1/2 | 246 | 152 | 65 | 29 | 9 7/10 | 6 | 7.04 / 14.08 | 16.96 / 33.92 |
| 7 | 7, 7 1/2 | 254 | 158 | 67 | 29 | 10 | 6 1/4 | 7.28 / 14.56 | 17.20 / 34.40 |
| 8 | 8, 8 1/2 | 262 | 164 | 69 | 29 | 10 3/10 | 6 7/16 | 7.52 / 15.04 | 17.44 / 34.88 |
| 9 | 9, 9 1/2 | 270 | 170 | 71 | 29 | 10 3/5 | 6 11/16 | 7.76 / 15.52 | 17.68 / 35.36 |
| 10 | 10, 10 1/2 | 278 | 176 | 73 | 29 | 10 19/20 | 6 15/16 | 8.04 / 16.08 | 17.96 / 35.92 |
| 11 | 11, 11 1/2 | 286 | 182 | 75 | 29 | 11 1/4 | 7 3/16 | 8.24 / 16.48 | 18.16 / 36.32 |
| 12 | 12, 12 1/2 | 294 | 188 | 77 | 29 | 11 11/20 | 7 7/16 | 8.40 / 16.80 | 18.32 / 36.64 |
| 13 | 13 | 302 | 194 | 79 | 29 | 11 9/10 | 7 5/8 | 8.64 / 17.28 | 18.56 / 37.12 |

*Toe length is distance from center of front axle to front end of plate

**Heel length is distance from center of back axle to back end of plate

***Plate assembly includes king pins, trucks, cushions, retainers, lock nuts