

SURE-GRIP INTERNATIONAL

DISTANCE FROM AXLE TO AXLE (INCHES)

OVERALL PLATE LENGTH

PLATE	0000	000	00	0	1	2	3	4	5	6	7	8	9	10
Super X				8	8.4	8.6	9	9.5	10.2	10.6	11	11.4	11.8	
Jogger					9.2	9.4	9.8	10	10.4	10.8	11.2	11.5	11.8	12.2
Competitor				8.2	8.7	9	9.6	10	10.4	10.8	11.2	11.6	12	
Invader				8.4	8.8	9.2	9.6	10	10.4	10.8	11.2	11.6	12	
CYCLONE, XK4														
CENTURY, CLASSIC	7.4	7.6	7.8	8	8.2	8.6	9	9.4	9.8	10.2	10.6	11	11.4	
Probe / Rock					8.2	8.6	9	9.4	9.8	10.2	10.6	11	11.4	

AXLE DISTANCE

PLATE				0	1	2	3	4	5	6	7	8	9	10
Super X				4.6	5	5.2	5.6	6.1	6.8	7.2	7.7	8.1	8.5	
Jogger					5.3	5.5	5.9	6.1	6.5	6.9	7.3	7.6	7.9	8.3
Competitor				4.1	4.6	4.8	5.4	5.8	6.2	6.6	7	7.4	8	
Cerntury	3.2	3.4	3.6	4	4.4	4.9	5.2	5.6	6	6.4	6.8	7.2	7.6	
Classic	3.2	3.4	3.6	4	4.4	4.9	5.2	5.6	6	6.4	6.8	7.2	7.6	
Invader SA45				4.7	5.1	5.5	5.9	6.3	6.7	7.1	7.5	7.9	8.3	
Invader DA45				5	5.4	5.8	6.2	6.7	7.1	7.5	7.9	8.3	8.7	
Cyclone SA45				4.8	5.2	5.6	6	6.4	6.8	7.2	7.6	8	8.3	
XK-4 SA45	4.4	4.6	4.8	5	5.2	5.6	6	6.4	6.8	7.2	7.6	8	8.3	
XK-4 DA45	4.6	4.8	5	5.2	5.4	5.8	6.2	6.6	7	7.4	7.8	8.2	8.5	
XK-4 DA10	3.6	3.8	4	4.2	4.4	4.9	5.2	5.6	6	6.4	6.8	7.2	7.6	
Probe / Rock					4.2	4.6	5	5.4	5.8	6.2	6.6	7	7.4	